

MODIS PAR

(Photosynthetically Active Radiation)

Product Description

This Level 2 and 3 product consists of four related parameters which describe the irradiance at the ocean surface. The first is Downwelling Solar Irradiance (Param. 5354) which is the incident irradiance just above the sea surface in each of the visible MODIS ocean bands (8, 9, 10, 11, 12, 13, 14). The second is Instantaneous Photosynthetically Active Radiation, Param. 2266 (IPAR), which is the total downwelling flux of photons just below the sea surface at the instant MODIS views the pixel integrated over the wavelength range of 400 to 700 nm. The third is PAR (Param. 2330) which is the irradiance averaged over an entire day. Since measurements are only available at the time MODIS views the pixel, this parameter is estimated from IPAR by the algorithm. The product is produced at 1 km daily for Level 2 and gridded at Level 3 daily and weekly at 1 km. The fourth is ARP (absorbed radiation by phytoplankton) averaged over the first optical depth. This parameter is critical for calculation of fluorescence efficiency, a product useful for conditioning photosynthesis models (MOD 23).

Research & Applications

This product is critical for determining photosynthetic rate of growth of phytoplankton and primary ocean production. Downwelling irradiance is needed as an input to the chlorophyll *a* algorithm (MOD 21) and it is used to convert the normalized water-leaving radiance values (MOD 18) into remote-sensing reflectance values. A series of irradiance models specific for terrigenous aerosols have been available; however, the aerosol characteristics of these models differ greatly in size and optical characteristics from marine aerosols. The irradiance model of Gregg and Carder (1990) uses a mixture of marine and terrigenous aerosols and forms the basis for the algorithm for MODIS PAR product.

Data Set Evolution

Product generation begins with solar irradiance data at 1 nm resolution which is taken from the revised Neckel and Labs data and corrected for Earth-Sun

distance for the current day. Atmospheric correction is made for the effects of scattering, absorption by ozone, absorption by gas, and water vapor. This spectrum is then binned and weighted appropriately to give the irradiance in each of the MODIS ocean bands. Next, the below-surface values are computed and summed to give IPAR. Inputs to the algorithm are Water Leaving Radiance (MOD 18), PAR (MOD 22) and Absorption Coefficient (MOD 36).

Suggested Reading

- Gordon, H.R. and M. Wang, 1994.
- Gregg, W.W. and K.L. Carder, 1990.
- Iqbal, M., 1983.
- Paltridge, G.W., and C.M.R. Platt, 1976.

MOD 22 PRODUCT SUMMARY

Coverage:

global ocean surface, clear-sky only

Spatial/Temporal Characteristics:

1 km/daily, weekly

Key Science Applications:

ocean chlorophyll, productivity

Key Geophysical Parameters:

photosynthetically available irradiance

Processing Level:

2, 3

Product Type:

Validation, at-launch

Science Team Contact:

K. Carder, D. Tanré,
W. Esaias, M. Abbott